



► Temperature range:

- ✓ -50 °C to 150 °C
- ✓ -58 °F to 302 °F



► With hook device



Flexible: Digital puncture thermometer for core temperature measurement in the freezing range or during food preparation.

- | | | | |
|----------------------------------|---|-----------|------------------------|
| • Control unit: | Electronic | • Size: | W 151 x D 15 x H 20 mm |
| • Puncture depth: | 67 mm | • Weight: | 0.03 kg |
| • Temperature range: | -50 °C to 150 °C | | |
| • Design: | Digital | | |
| • With temperature sensor: | Yes | | |
| • Designed for: | Core temperature measurements
Temperature monitoring during transport and storage | | |
| • Colour: | Black | | |
| • Temperature measurement units: | °C
°F | | |
| • Material temperature sensor: | Stainless steel | | |
| • Diameter temperature sensor: | 4 mm | | |
| • Material: | Plastic | | |
| • Application area: | Canteens
Refrigerated rooms
Refrigeration cell | | |
| • Properties: | Memory function
Automatic shutdown after 25 minutes
LCD display
Temperature range also in Fahrenheit
With suspension device | | |
| • Size of display field: | W 21,75 x H 7,5 mm | | |
| • Battery: | Button cell LR44/AG13 | | |
| • Including: | Protection cap
1 battery | | |
| • Important information: | Do not use in oven | | |