



► Up to 7 x 1/1 GN or 600 x 400 mm



► Easy knob operation



► Double door glazing, inner door can be opened easily for cleaning




► Vapour extractor is easy to regulate



► Bearing rails can be detached



► 2 fan speed settings



The Bartscher combi steamer from the Silversteam series has 7 shelves in 1/1 GN format – it's the ideal partner for every kitchen. The manual controls enable the easy, on-demand control of all cooking processes.

- | | | | |
|---------------------------------------|--|--------------------------|--|
| • Power load: | 9,6 kW 400 V 50 Hz | • Properties: | Rounded baking chamber
Bearing rails can be detached
Double-winged door pane
LED lighting in door
Socket (500 W) for connection of an extractor hood |
| • Equipment connection: | 3 NAC | • LED display: | Steaming
Core temperature
Temperature
Time |
| • Temperature range: | 50 °C to 280 °C | • Including: | 1 grille 1/1 GN
1 tray 1/1 GN
1 water supply hose |
| • Control unit: | Toggle | • Available on request: | - |
| • Functions: | Circulating air
Steam
Combi-steaming
Low temperature cooking
Reversing motor direction (fan wheels)
Steam production by means of direct injection | • Control lamp: | ON/OFF
Temperature
Silversteam
Stepless |
| • Rack control: | No | • Series: | Silversteam |
| • Continuous operation: | Yes | • Temperature control: | Stepless |
| • Vapour extractor: | Yes | • Interior lighting: | Yes |
| • Core temperature sensor connection: | Side | • Format drawers: | 1/1 GN
600 x 400 mm |
| • USB connection: | - | • Operating mode: | Electro |
| • Number of cooking programs: | 1 | • With cleaning system: | No |
| • Fan speed: | 2 levels | • Material: | CNS 18/10 |
| • Number of cooking phases: | 1 | • Important information: | From a water hardness of 5° d.H upwards, we urgently recommend fitting a suitable water softener and a water pressure of maximum 3 bar |
| • Type of drawers: | Crosswise | • Size: | W 890 x D 835 x H 850 mm |
| • Number of drawers: | 7 | • Weight: | 101 kg |
| • Distance between trays: | 74 mm | | |
| • Water connection: | 3/4" | | |
| • Time adjustment: | 0 to 120 minutes | | |
| • Material cooking chamber: | CNS 18/10 | | |
| • Number of motors: | 2 | | |