BLUE SEAL EVOLUTION SERIES®

Technical data sheet for SINGLE PAN ELECTRIC PASTA COOKER 450mm

E47, E47-7

- High performance single pan pasta cooker E47 10.5kW 3 phase E47-7 7.0kW 1 phase
- Heavy-duty 3 coil Incoloy 825 element
- Easy clean 316 grade stainless steel open pan
- 40L water capacity
- Integrated water fill and starch skimming water faucet
- Six stainless steel pasta baskets supplied
- Hinged basket drain stand
- Safety cut-out thermostat for empty pan/water boil out
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular



E47

Overall Construction

- Pan 1.5mm 316 stainless steel
- Bull nose welded 1.5mm stainless steel
- Splashback 1.2mm stainless steel
- Side panels 1.2mm stainless steel
- Double skin door with 0.9mm stainless exterior
- 25mm (1") skimming overflow and pan drains drain valve
- 63mm dia. heavy-duty 1.2mm stainless steel legs with adjustable feet
- 6 stainless steel baskets with moulded handles
- Stainless steel wire basket support grid in pan

Controls

- Large easy to use knob heat resistant reinforced
- 3 power settings (boil-simmer-standby)
- Mechanical thermostat
- Thermostat range 30°C 110°C
- Fail safe over-temperature safety cut-out
- Element tilt switch for heating cut-out
- Indicator lights for power & heating
- Fine adjustment water faucet for pan filling and water refreshing/ starch skimming

Cleaning and Servicing

- Open stainless steel pan for easy clean
- Hinged basket drain stand
- Removable basket support grid
- 25mm (1") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit

Technical data sheet for SINGLE PAN ELECTRIC PASTA COOKER 450mm

Specifications

Pan Size Water capacity 40L Width 365mm Length 405mm Basket immersion depth 165mm

Baskets

6 stainless steel perforated baskets with moulded plastic handles 125mm x 165mm x 180mm deep Stainless steel wire basket support grid

Elements

1 x 10.5kW Incoloy 825 heating element (E47) 1 x 7.0kW Incoloy 825 heating element (E47-7)

Electrical Requirements E47

10.5kW, 400-415V, 50/60Hz, 3P+N+E L1 14.6A L2 14.6A L3 14.6A

E47-7 7.0kW, 220-240V, 50/60Hz, 1P+N+E L1 29.2A

Electrical Connection 56mm from RH side, 541mm from rear and 489mm from floor

Water Connection Cold water connection 50mm from left hand side. 556mm from rear and 150mm from floor R¹/₂ (BSP) male

550kPa 80psi maximum water pressure

Drain Connection

Drain must be connected to system suitable for boiling water discharge 1" BSP Male connection 118mm from left hand side, 470mm from rear, and 170mm from floor

Dimensions

Width 450mm Depth 812mm Height 915mm Incl. splashback 1085mm

Nett weight 78kg


Packing data


0.54m3, 120kg Width 870mm Depth 495mm Height 1255mm

Options

Rectangular baskets 320mm x 165mm x 180mm deep Square baskets 165mm square x 180mm deep Side splash guards Joining caps

E47





OBLUE SEAL

www.blue-seal.co.uk www.bluesealevolution.com

United Kingdom

Blue Seal Limited Unit 67 Gravelly Business Park Gravelly Birmingham B24 8TQ England Telephone 0121-327 5575 Facsimile 0121-327 9711 Email sales@blue-seal.co.uk www.blue-seal.co.uk

Australia

Moffat Pty Limited 740 Springvale Rd Mulgrave Victoria 3170 Australia Telephone 03-9518 3888 Facsimile 03-9518 3833 Email vsales@moffat.com.au www.moffat.com.au

New Zealand

Moffat Limited Christchurch 45 Illinois Drive Izone Business Hub **Rolleston 7675** Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz



IS09001 Quality Management SGS Standard

MOFFAT

ISO9001 All Blue Seal products are designed and manufactured by Moffat using the internationally recognised IS09001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.



BLUE SEAL EVOLUTION SERIES®