




ELECTRIC FRYER - 10 L - COUNTERTOP


- External paneling in stainless steel
- Work surface in AISI 304, 1.2 mm thick
- Electric fryer with tank in AISI 304, with rounded corners and moulded bottom for thorough cleaning
- Moulded work surface with front raised edges to collect any oil overflow or foaming
- Heating with heating elements in AISI 304 stainless steel positioned inside the tank and liftable to facilitate cleaning of the tank itself
- The tank oil temperature is controlled by a mechanical thermostat with regulation between 100°C and 195°C
- Equipped with manual reset safety thermostat
- Bulbs protected against accidental impact
- · Fryer equipped with removable underlying grid for basket support,
- Oil drainage through a chrome pipe located on the control panel
- Single tank dimensions 238x348mm with 10 L capacity
- Ergonomic control panel with controls tilted toward the operator
- Indicator lights to monitor the correct operation of the appliance
- Height-adjustable stainless steel feet

GIORIK

TECHNICAL SPECIFICATIONS	
Dimensions (mm)	400x700x250
Volume (m³)	0,60
Weight (kg)	30

ELECTRICAL CONNECTI	ON
kW	10
Power supply	VAC 400/3N
	50/60Hz
Cold water inlet	





- (A) water fill
- (C) hot water fill
- (E) electrical input
- (F) cold water fill
- **G**) gas inlet
- (S) water drain

