



BGBF5P - Lincat Blu Blast Chiller - 5 Trays

Perfect for large batch cooking, where large quantities of food need to be brought down to storage temperature quickly

- Quickly and efficiently pull down the temperature of cooked foods
- Perfect for large batch cooking, where large quantities of food need to be brought down to storage temperature quickly
- Reduce a product's core temperature from 90°C to 3°C within 90 minutes
- With shock freezing cycle allows the nutritional properties, appearance and flavour of a product to be maintained after thawing
- Core probe needle as standard
- Indirect air flow guarantees a perfect temperature throughout the unit
- Side racks removable without tools for easy cleaning

- Easy-to-use digital controls simple buttons for soft blast chilling, hard blast chilling, and shock freezing cycles, as well as manual time/temperature controls
- Auto-defrost function
- Radiused interior corners enable easy cleaning
- Reversible self-closing door with 105 degree stop
- High efficiency 60mm cyclopentane insulation zero ODP (Ozone Depletion Potential) and only a low GWP (Global Warming Potential), providing excellent thermal efficiency
- Wide magnetic gasket gives effective seal, easily removable for cleaning
- Hygienic and robust design Grade 304 stainless steel interior and exterior, radiused interior corners to promote easy cleaning

Specifications

Summary		Power and Performance	
Brand	Lincat	Total Power kW	0.8
Range	Blu	Temperature Range °C	+20 to -40
Power Type	Electric	Temperature Control	Electronic
Unit Type	Free-standing	Cooling Capacity Watts	2,095W / 615W
Available in UK Only	No	Climate Class	5
UK Warranty	2 Years Parts and Labour (3 Years on Compressor)		
Export Warranty	Contact your local dealer		
GTIN	5056105123361		

Key Specifications Capacity Lockable Door **Gastronorm Capacity** GN1/1, Euronorm No **Number of Doors Chilling Capacity kg** 14 Reversible Door **Chilling Time mins** 90 Yes Freezing Capacity kg **Number of Shelf Positions** 5 8 Refrigerant Type R452a Freezing Time mins Construction/Finish 304 Grade S/S Ext/Int **Base Mounting** Insulation Material/Thickness Cyclopentane / 60 mm Maximum Ambient Temperature °C 38 **Auto Defrost** Yes **HACCP Compliant** Yes **Number of Shelves** 0 **Shelf Supports** Anti-tilt Integral Handle Self Close Door Yes





Weights and Dimensions		Supply Connections	
Unit Height (External) mm	850	Requires Installation	Yes
Unit Width (External) mm	800	Requires Electrical Supply	Yes
Unit Depth (External) mm	800	UK 3 Pin Plug	No
Net Weight Kg	105	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	800
		Single Phase Amps	5
		Single Phase Voltage	230
Shipping			
Packed Weight Kg	125		
Packed Height cm	102		
Packed Width cm	85		
	84		



Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

.

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm