Packed Weight Kg

Packed Height cm

Packed Width cm

Packed Depth cm

29.7

49.5

70

70

SILVERLINK 600



DF618 - Lincat Silverlink 600 Electric Counter-top Twin Tank Fryer - 2 Baskets - W 600 mm - 2 x 9.0 kW The Silverlink 600 Electric Twin Tank Counter Top Fryer not only provides greater versatility, but also increased power capable of delivering 60kg of chips per hour.

- Two independently operated fryer tanks for greater versatility, increased power delivers 60kg of chips per hour
- Front mounted controls for safety
- Hinged elements to give easy access during cleaning
- Cool zone collects cooking debris gives cleaner cooking results and saves money by prolonging the life of the oil
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Failsafe top temperature cut out ensures safe operation.
- Fully moulded 304 stainless steel tank and heavy duty nickel plated baskets for the most demanding of operations
- Front drain off tap for easy removal of cooking oil

Specifications				
Summary		Power and Performance		
Brand Range Power Type Unit Type Available in UK Only	Lincat Silverlink 600 Electric Counter-top No	Total Power kW Temperature Range °C IP Rating Temperature Control	2 x 9.0 130-190 IP33 Mechanical	
UK Warranty Export Warranty GTIN Key Specifications	2 Years Parts and Labour Warranty Contact your local dealer 5056105104650	Capacity		
Number of Baskets Number of Tanks Gravity Filtration Pumped Filtration Drain Location	2 2 No No Front-mounted	Product Output per Hour Capacity Litres	52kg chips - 12mm [frozen], 60kg chips - 12mm [chi 2 x 9.0	
Weights and Dimensions		Supply Connections		
Unit Height (External) mm Unit Width (External) mm	330 600	Requires Installation Requires Electrical Supply	Yes Yes	


Weights and Difference		Supply Sollinosticine	cupply connections	
Unit Height (External) mm	330	Requires Installation	Yes	
Unit Width (External) mm	600	Requires Electrical Supply	Yes	
Unit Depth (External) mm	632	UK 3 Pin Plug	No	
Net Weight Kg	27	Requires Hardwiring	Yes	
		Electrical Supply Rating Watts	2 × 9,000	
		Single Phase Amps	2 × 39.0	
		Single Phase Voltage	230	
		Three Phase Amps	L1=2 x 13.0; L2=2 x 13.0; L3=2 x 13.0	
		Three Phase Voltage	400	
Shipping				





Available Accessories


BA96	BASKET SPUN DFSMALL
CC6	Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm
CN6	Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
HC6	Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
HCL6	Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW
SLS6	Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm

Technical Picture















Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Officed Mingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm



Product Code: DF618 Page Number: 3 Print Date: 23/06/2023