



## iCP062E/LH - RATIONAL iCombi Pro - Model 6-2/1 -Electric Free-standing Combi Oven - 22.4 kW

The intelligent RATIONAL iCombi Pro 6-2/1 thinks, learns, watches and adapts, dynamically responding to requirements.

- 6 x GN 2/1 capacity, ideal for restaurants and foodservice applications
- Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- iCookingSuite continuously checks the condition of the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process

- iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same time
- iCareSystem 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- WiFi interface for connected cooking and easy access to HACCP documentation
- Left hinged door

| Summary                   |                                   | Power and Performance                 |                                  |
|---------------------------|-----------------------------------|---------------------------------------|----------------------------------|
|                           |                                   | Tonor and Fortormance                 |                                  |
| Brand                     | Lincat                            | Total Power kW                        | 22.4                             |
| Range                     | RATIONAL                          | Temperature Range °C                  | 30-300                           |
| Series                    | iCombi Pro                        | IP Rating                             | IPX5                             |
| Power Type                | Electric                          | Temperature Control                   | Electronic                       |
| Unit Type                 | Free-standing                     | Oven Rating kW                        | Steam connection = 18.0; Hot air |
| Available in UK Only      | Yes                               |                                       | connection = 21.6                |
| UK Warranty               | RATIONAL 2 Years Parts and Labour |                                       |                                  |
|                           | Warranty                          |                                       |                                  |
| Key Specifications        |                                   | Capacity                              |                                  |
| Type of Lighting          | LED                               | Gastronorm Capacity                   | 6 x GN2/1                        |
| Number of Grids included  | 0                                 | Portions per Day                      | 60-160                           |
| Weights and Dimensions    |                                   | Supply Connections                    |                                  |
| Unit Height (External) mm | 804                               | Requires Installation                 | Yes                              |
| Unit Width (External) mm  | 1072                              | Requires Electrical Supply            | Yes                              |
| Unit Depth (External) mm  | 1042                              | UK 3 Pin Plug                         | No                               |
| Net Weight Kg             | 137                               | Requires Hardwiring                   | Yes                              |
|                           |                                   | <b>Electrical Supply Rating Watts</b> | 22,400                           |
|                           |                                   | Three Phase Amps                      | L1=35.0; L2=35.0; L3=35.0        |
|                           |                                   | Three Phase Voltage                   | 400                              |
|                           |                                   | Water Connection Pressure Bar         | 6                                |
|                           |                                   | Drain Connection                      | DN 50 mm                         |
|                           |                                   | Water Connection                      | 3/4"                             |





## **Shipping**

Packed Weight Kg150.7Packed Height cm96Packed Width cm117.5Packed Depth cm115.5

## **Available Accessories**

60.70.464

RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS  $\,$ 



**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

company no. 21/01 h

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday – Friday:

8.30am - 5pm

Product Code: ICP062E/LH Page Number: 2 Print Date: 28/10/2022