



ICP101E/LH - RATIONAL iCombi Pro - Model 10-1/1 - Electric Freestanding Combi Oven -18.9 kW

- 10 x GN 1/1 capacity, ideal for restaurants and foodservice applications
- Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- iCookingSuite continuously checks the condition of the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process

The intelligent RATIONAL iCombi Pro 10-1/1 thinks, learns, watches and adapts, dynamically responding to requirements.

- iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same time
- iCareSystem 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- WiFi interface for connected cooking and easy access to HACCP documentation

Left hinged door

Specifications			
Summary		Power and Performance	
Brand	Lincat	Total Power kW	18.9
Range	RATIONAL	Temperature Range °C	30-300
Series	iCombi Pro	IP Rating	IPX5
Power Type	Electric	Temperature Control	Electronic
Unit Type	Free-standing	Oven Rating kW	Steam connection = 18.0;Hot air
Available in UK Only	Yes		connection = 18.0
UK Warranty	RATIONAL 2 Years Parts and Labour Warranty		
Key Specifications		Capacity	
Type of Lighting	LED	Gastronorm Capacity	10 × GN1/1
Number of Grids included	0	Portions per Day	80-150
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	1064	Requires Installation	Yes
Unit Width (External) mm	850	Requires Electrical Supply	Yes
Unit Depth (External) mm	842	UK 3 Pin Plug	No
Net Weight Kg	127	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	18,900
		Three Phase Amps	L1=32.0; L2=32.0; L3=32.0
		Three Phase Voltage	400
		Water Connection Pressure Bar	6
		Drain Connection	DN 50 mm
		Water Connection	3/4"





ShippingPacked Weight Kg139.7Packed Height cm125Packed Width cm93.5Packed Depth cm95.5

Available Accessories

60.70.464

RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS

Lincat fift

Lincat Limited

Whisby Road, Lincoln, LN6 30Z,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm