UK Warranty





ICP101G/N - RATIONAL iCombi Pro - Model 10-1/1 - Natural Gas Freestanding Combi Oven - 22 kW

The intelligent RATIONAL iCombi Pro 10-1/1 thinks, learns, watches and adapts, dynamically responding to requirements.

- $10 \times GN 1/1$ capacity, ideal for restaurants and foodservice applications
- Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- $i Cooking Suite\ continuously\ checks\ the\ condition\ of$ the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process

- iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same
- iCareSystem 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- WiFi interface for connected cooking and easy access to HACCP documentation

Specifications Summary Power and Performance Brand Total Power kW Lincat 22 Range

Warranty

RATIONAL Temperature Range °C 30-300 Series IP Rating IPX5 iCombi Pro **Temperature Control Power Type** Flectronic

Steam connection = 20.0; Hot air Gas Type Natural Gas Oven Rating kW connection = 22.0 **Unit Type** Free-standing

Available in UK Only RATIONAL 2 Years Parts and Labour

Key Specifications Capacity Type of Lighting **Gastronorm Capacity** 10 x GN1/1 LED **Number of Grids included** Ω Portions per Day 80-150





Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	1064	Requires Installation	Yes	
Unit Width (External) mm	850	Requires Electrical Supply	Yes	
Unit Depth (External) mm	842	UK 3 Pin Plug	Yes	
Net Weight Kg	155	Requires Hardwiring	No	
		Electrical Supply Rating Watts	900	
		Single Phase Amps	13	
		Single Phase Voltage	230	
		Gas Connection BSP	3/4"	
		Gas Pressure Natural mbar	18-25	
		Total heat input at full rate Natural kW	22	
		Water Connection Pressure Bar	6	
		Drain Connection	DN 50 mm	
		Water Connection	3/4"	

Shipping

 Packed Weight Kg
 170.5

 Packed Height cm
 125

 Packed Width cm
 93.5

 Packed Depth cm
 95.5

Available Accessories

60.70.464

RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS $\,$



Lincat Limited Customer Care

Whisby Road, **Tel:** +44 1522 875500

Lincoln, LN6 3QZ, **Email:** care@lincat.co.uk

United Kingdom

Company No: 2175448

A member company of

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday – Friday:

8.30am - 5pm