UK Warranty





ICP102G/P - RATIONAL iCombi Pro - Model 10-2/1 - Propane Gas Freestanding Combi Oven - 40 kW

The intelligent RATIONAL iCombi Pro 10-2/1 thinks, learns, watches and adapts, dynamically responding to requirements.

- $10 \times GN$ 2/1 capacity, ideal for restaurants and foodservice applications
- Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- $i Cooking Suite\ continuously\ checks\ the\ condition\ of$ the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process

- iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same
- iCareSystem 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- WiFi interface for connected cooking and easy access to HACCP documentation

Specifications Summary Power and Performance Brand Total Power kW Lincat 40 Range RATIONAL Temperature Range °C

Warranty

30-300 Series IP Rating IPX5 iCombi Pro Power Type **Temperature Control** Flectronic Gas Type Propane Gas Steam connection = 40.0; Hot air

Oven Rating kW connection = 40.0 **Unit Type** Free-standing

Available in UK Only RATIONAL 2 Years Parts and Labour

Key Specifications Capacity Type of Lighting **Gastronorm Capacity** LED 10 x GN2/1 **Number of Grids included** Ω Portions per Day 150-300





Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	1064	Requires Installation	Yes	
Unit Width (External) mm	1072	Requires Electrical Supply	Yes	
Unit Depth (External) mm	1042	UK 3 Pin Plug	Yes	
Net Weight Kg	192	Requires Hardwiring	No	
		Electrical Supply Rating Watts	1,500	
		Single Phase Amps	13	
		Single Phase Voltage	230	
		Gas Connection BSP	3/4"	
		Gas Pressure Propane mbar	25-57.5	
		Total heat input at full rate Propane kW	40	
		Water Connection Pressure Bar	6	
		Drain Connection	DN 50 mm	
		Water Connection	3/4"	
01.1				

Shipping

 Packed Weight Kg
 211.2

 Packed Height cm
 125

 Packed Width cm
 117.5

 Packed Depth cm
 115.5

Available Accessories

60.70.464

RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS $\,$



Lincat Limited

Whisby Road, **Tel:** +44 1522 875500

Lincoln, LN6 3QZ, **Email:** care@lincat.co.uk

Customer Care

United Kingdom

Company No: 2175448

A member company of

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday – Friday:

8.30am - 5pm