



ICP202E - RATIONAL iCombi Pro - Model 20- 2/1 - Electric Free- standing Combi Oven - 67.9 kW

The intelligent RATIONAL iCombi Pro 20-2/1 thinks, learns, watches and adapts, dynamically responding to requirements.

- ✓ Large 20 x GN 2/1 capacity, ideal for mass catering and for food service establishments with high output requirements
- ✓ Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- ✓ iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- ✓ iCookingSuite continuously checks the condition of the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process
- ✓ iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same time
- ✓ iCareSystem - 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- ✓ WiFi interface for connected cooking and easy access to HACCP documentation

Specifications

Summary

Brand	Lincat
Range	RATIONAL
Series	iCombi Pro
Power Type	Electric
Unit Type	Free-standing
Available in UK Only	Yes
UK Warranty	RATIONAL 2 Years Parts and Labour Warranty

Power and Performance

Total Power kW	67.9
Temperature Range °C	30-300
IP Rating	IPX5
Temperature Control	Electronic
Oven Rating kW	Steam connection = 54.0; Hot air connection = 66.0

Key Specifications

Type of Lighting	LED
Number of Grids included	0

Capacity

Gastronorm Capacity	20 x GN2/1
Portions per Day	300-500

Weights and Dimensions

Unit Height (External) mm	1872
Unit Width (External) mm	1082
Unit Depth (External) mm	1117
Net Weight Kg	336

Supply Connections

Requires Installation	Yes
Requires Electrical Supply	Yes
UK 3 Pin Plug	No
Requires Hardwiring	Yes
Electrical Supply Rating Watts	67,900
Three Phase Amps	L1=100.0; L2=100.0; L3=100.0
Three Phase Voltage	400
Water Connection Pressure Bar	6
Drain Connection	DN 50 mm
Water Connection	3/4"

Shipping

Packed Weight Kg	369.6
Packed Height cm	204.3
Packed Width cm	119
Packed Depth cm	121.8

Available Accessories

60.70.464 RATIONAL Appliarence Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm