Lincat Combi Ovens



LCSH106I - Lincat
CombiSlim 1.06 Electric
Counter-top Combi Oven
with Hoodini - Injection W 513 mm - 8.4 + 2.2 kW

Choose CombiSlim with a Ventless Hoodini solution, to gain maximum flexibility using minimum space.

- Ideal for where venting to the atmosphere is impractical, allow the setup of a cooking station in previously unsuitable areas of a building
- Utilise non-traditional spaces in the kitchen, front of house or back bar to diversify operations
- Gain maximum flexibility using minimum space with CombiSlim ovens. These combi ovens measure only 51.4 cm in width and fit into all professional kitchens
- CombiSlim ovens are ideal for small-scale food production in take-away shops, cafés, etc
- Intuitive touch display SmartTouch® for programming

- 1/1GN compatible
- Steam injection, with CombiSmart® humidity control
- Ability to create cooking programmes with up 15 stens
- Rack timer allowing accurate cooking times for different items on different shelves
- Two-step safety handle

400

2.5-6

3/4"

DN 40 mm

Summary		Power and Performance	
Brand	Lincat	Total Power kW	8.4+2.2
Range	Lincat Combi Ovens	Temperature Range °C	30-300
Series	CombiSlim	IP Rating	IPX5
Power Type	Electric	Temperature Control	Electronic
Unit Type	Counter-top	·	Steam connection = N/A:Hot air
Available in UK Only	Yes	Oven Rating kW	connection = 8.4
UK Warranty	2 Years Parts and Labour Warranty		
GTIN	5056105121763		
Key Specifications		Capacity	
Type of Lighting	Halogen	Gastronorm Capacity	6 x GN1/1 (20mm deep)
Number of Grids included	0	Portions per Day	60
Weights and Dimensions		Supply Connections	
	1174	Requires Installation	Yes
Unit Height (External) mm			
Unit Height (External) mm Unit Width (External) mm	514	Requires Electrical Supply	Yes
• ' '	514 962	Requires Electrical Supply UK 3 Pin Plug	Yes Yes
Unit Width (External) mm			
Unit Width (External) mm Unit Depth (External) mm	962	UK 3 Pin Plug	Yes
Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm	962 350	UK 3 Pin Plug Requires Hardwiring	Yes Yes
Unit Width (External) mm Unit Depth (External) mm Height (Internal) mm Width (Internal) mm	962 350 400	UK 3 Pin Plug Requires Hardwiring Electrical Supply Rating Watts	Yes Yes 8,400 + 2,200

Three Phase Voltage

Drain Connection

Water Connection

Water Connection Pressure Bar



Lincat Combi Ovens

Shipping

Packed Weight Kg Packed Height cm 123.8 Packed Width cm 80 Packed Depth cm

Available Accessories

LCA3003 Lincat Combi Oven Imperial Non-stick Container - GN1/1 (325 x 530 mm) - 20 mm deep LCA3005 Lincat Combi Oven Imperial Non-stick Container - GN1/1 (325 x 530 mm) - 40 mm deep LCA3007 Lincat Combi Oven Imperial Non-stick Container - GN1/1(325 x 530 mm) - 60 mm deep LCA3009 Lincat Combi Oven Imperial Pizza and Grilling Sheet - GN1/1 (325 x 530 mm)

LCA3011 Lincat Combi Oven Imperial Grilling Grid - GN1/1(325 x 530 mm)

LCA3012 Lincat Combi Oven Imperial Potato Grid - GN1/1(325 x 530 mm) - 28 Potato Capacity

LCA3013 Lincat Combi Oven Imperial Multi-tray - 8 Moulds - GN1/1(325 x 530 mm)

LCA3015 Lincat Combi Oven Non-stick Aluminium Baking Sheet - GN1/1 (325 x 530 mm)

LCA3017 Lincat Combi Oven Non-stick Perforated Aluminium Baking Sheet - GN1/1 (325 x 530 mm)

LCA3019 Lincat Combi Oven Silicone Baking Mat - GN1/1 (325 x 530 mm) LCA3021 Lincat Combi Oven Steamfry Basket - GN1/1 (325 x 530 mm) LCA3023 Lincat Combi Oven Rack for Spare Ribs - GN1/1(325 x 530 mm)

LCA3024 Lincat Combi Oven Chicken Grid - GN1/2 (325 x 265 mm) - 4 Chicken Capacity LCA3025 Lincat Combi Oven Chicken Grid - GN1/1 (325 x 530 mm) - 8 Chicken Capacity

LCA4001 Lincat Combi Oven Software Key - Quick Select Recipes (QSR) LCA6006 Lincat Combi Oven Static Stand for CombiSlim - Open Stand

LCA6007 Support Rail Cassette for LCA6006 Stand for CombiSlim - 10 Support Rails

LCC1001 Hydro Shield 3600 (L) Water Filter Cartridge - Recommended for CombiSlim and Visual Cooking 1.06/1.10

Hydro Shield 6000 (XL) Water Filter Cartridge - Recommended for Visual Cooking 1.20/2.06/2.10/2.20 and all Combi Ovens in hard LCC1002

water areas

Hydro Shield 3600 (L) Water Filter Kit - Including Filter, Filter Head and Hose - Recommended for CombiSlim and Visual Cooking LCC1003

Hydro Shield 6000 (XL) Water Filter Kit - Including Filter, Filter Head and Hose - Recommended for 1.20/2.06/2.10/2.20 + all Ovens in LCC1004

hard water areas

LCC2003 Lincat Protect Intense Detergent - 2 x 5I

LCC2005 Lincat Protect Cleaning Package - 6 x 5l Intense Detergent and 2 x 5l Rinse Aid

LCC2006 Lincat Protect Rinse Aid - 2 x 5I

OCG8111 1/1 GN GRID-S/STEEL - P/NO. GN1/1-1D6 20D3



Customer Care

Whisby Road, Tel: +44 1522 875500

Lincoln, LN6 3QZ, Email: care@lincat.co.uk

Company No: 2175448

A member company of

Lincat Limited

United Kingdom

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm

Product Code: LCSH106I Print Date: 27/10/2022 Page Number: 2