



SL422L12GO - FriFri Super Easy 422 Electric Free-standing Twin Tank Fryer with Filtration - 2 Baskets - W 400 mm - 2 x 7.5 kW - Single Phase When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A free standing Super Easy 422 offers outstanding value with no compromise in quality or performance.

- Outstanding quality with no compromise in quality or performance.
- Mechanical thermostat maintains oil to within +/-8
 °C of the temperature selected.
- Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- Keeping your oil in peak condition! Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri© filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes - so easy there is no excuse not to!
- Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- Optimum Allergy Control. Supplied with separate oil buckets, and can be supplied with separate pumped filtration systems, providing completely segregated gravity filtration for optimum allergen control or to cater for dietary preferences.

```
 Single phase.
```

230

2

Specifications			
Summary		Power and Performance	
Brand	FriFri	Total Power kW	2 x 7.5
Range	Super Easy	Temperature Range °C	95-190
Power Type	Electric	IP Rating	IPX4
Unit Type	Free-standing	Temperature Control	Mechanical
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105122777		
Key Specifications		Capacity	
Number of Baskets	2	Product Output per Hour	2 x 17kg fries - 7mm [frozen]
Number of Tanks	2	Capacity Litres	2×7.5-9.0
Gravity Filtration	Yes		
Pumped Filtration	No		
Drain Location	Through the body		
Weights and Dimensions		Supply Connections	

			cappy compensation	
Unit Height (External) mm	986	Requires Installation	Yes	
Unit Width (External) mm	397.5	Requires Electrical Supply	Yes	
Unit Depth (External) mm	650	UK 3 Pin Plug	No	
Net Weight Kg	56	Requires Hardwiring	Yes	
		Electrical Supply Rating Watts	2 x 7,500	
		Single Phase Amps	2×32.6	

Single Phase Voltage

Number of Supply Cables



ShippingPacked Weight Kg59.95Packed Height cm113Packed Width cm79Packed Depth cm52

Available Options		
Oil Pump		
OP1	1 Oil Pump	
OP2	2 Oil Pumps	
Legs/Castors		
OC200	OC200 - 2 Castors[Fixed at Rear]+ 2 Legs[at Front]	
OC400	0C400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]	

Lincat fift

Lincat Limited

Whisby Road, Lincoln, LN6 30Z,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm