



Packed Depth cm

SL422L32N0-

When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A free standing Super Easy 422 offers outstanding value with no compromise in quality or performance.

- Outstanding quality with no compromise in quality or performance.
- Mechanical thermostat maintains oil to within +/-8
 °C of the temperature selected.
- Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- Supplied with separate oil buckets.

| Summary | | Power and Performance | |
|--------------------------------------|-----------------------------------|--------------------------------|---------------------------------------|
| Drawd | E : E : | Total Power kW | 0.75 |
| Brand | FriFri | | 2 x 7.5 |
| Range | Super Easy | Temperature Range °C | 95-190 |
| Power Type | Electric | IP Rating | IPX4 |
| Unit Type | Free-standing | Temperature Control | Mechanical |
| Available in UK Only | No | | |
| JK Warranty | 2 Years Parts and Labour Warranty | | |
| Export Warranty | Contact your local dealer | | |
| GTIN | 5056105123606 | | |
| Key Specifications | | Capacity | |
| Number of Baskets | 2 | Product Output per Hour | 2 x 17kg fries - 7mm [frozen] |
| Number of Tanks | 2 | Capacity Litres | 2×7.5-9.0 |
| Gravity Filtration | No | | |
| Pumped Filtration | No | | |
| Drain Location | Through the body | | |
| Weights and Dimensions | | Supply Connections | |
| Unit Height (External) mm | 986 | Requires Installation | Yes |
| Unit Width (External) mm | 397.5 | Requires Electrical Supply | Yes |
| Unit Depth (External) mm | 650 | UK 3 Pin Plug | No |
| Net Weight Kg | 75.5 | Requires Hardwiring | Yes |
| Net Weight hg | 75.5 | Electrical Supply Rating Watts | 2 x 7,500 |
| | | Three Phase Amps | |
| | | • | L1=2 x 10.9; L2=2 x 10.9; L3=2 x 10.9 |
| | | Three Phase Voltage | 400 |
| | | Number of Supply Cables | 2 |
| Shipping | | | |
| | | | |
| Packed Weight Kg | 82 | | |
| Packed Weight Kg Packed Height cm | 82 113 | | |





Available Options

Legs/Castors

OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front]

OC400 OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]



Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Omica migaom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm