



SL622H32G0 - FriFri Super Easy 622 Electric Free-standing Twin Tank Fryer with Filtration - 2 Baskets - W 600 mm - 2 x 15.0 kW

When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A free standing Super Easy 622 offers outstanding value with no compromise in quality or performance.

- ✓ Outstanding quality with no compromise in quality or performance.
- ✓ Mechanical thermostat maintains oil to within +/-8 °C of the temperature selected.
- ✓ Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- ✓ Keeping your oil in peak condition! Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri© filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes – so easy there is no excuse not to!
- ✓ Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- ✓ Optimum Allergy Control. Supplied with separate oil buckets, and can be supplied with separate pumped filtration systems, providing completely segregated gravity filtration for optimum allergen control or to cater for dietary preferences.

Specifications

Summary		Power and Performance	
Brand	FriFri	Total Power kW	2 x 15.0
Range	Super Easy	Temperature Range °C	95-190
Power Type	Electric	IP Rating	IPX4
Unit Type	Free-standing	Temperature Control	Mechanical
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105122814		

Key Specifications		Capacity	
Number of Baskets	2	Product Output per Hour	2 x 26.5kg fries - 7mm [frozen]
Number of Tanks	2	Capacity Litres	2 x 12.5-14.5
Gravity Filtration	Yes		
Pumped Filtration	No		
Drain Location	Through the body		

Weights and Dimensions

Unit Height (External) mm	986
Unit Width (External) mm	592
Unit Depth (External) mm	650
Net Weight Kg	98.5

Supply Connections

Requires Installation	Yes
Requires Electrical Supply	Yes
UK 3 Pin Plug	No
Requires Hardwiring	Yes
Electrical Supply Rating Watts	2 x 15,000
Three Phase Amps	L1=2 x 21.7; L2=2 x 21.7; L3=2 x 21.7
Three Phase Voltage	400
Number of Supply Cables	2

Shipping

Packed Weight Kg	87.45
Packed Height cm	113
Packed Width cm	79
Packed Depth cm	72

Available Options

Oil Pump

OP1	1 Oil Pump
OP2	2 Oil Pumps

Baskets

622_2_BASKETS	2 Baskets
622_3_BASKETS	3 Baskets
622_4_BASKETS	4 Baskets

Legs/Castors

OC200	OC200 - 2 Castors [Fixed at Rear] + 2 Legs [at Front]
OC400	OC400 - 4 Castors [2 Fixed at Rear + 2 Swivel at Front]

Available Accessories

FZ301093	SMALL BASKET FOR 311 - COMPLETE WITH HANDLE
----------	---



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm