

GN 1/1



GN 1/1 + GN 2/1



AGRE-50
ACGE-50

AGRE-125
ACGE-125

mod.	range °C	length (mm)	height (mm)	depth (mm)	shelves GN 1/1	shelves GN 2/1	slides sets	capacity (L)	voltage	refrigerant	frig. power W	power W
AGRE-50	-2°C +8°C	460	2075	665	3	0	3	303	230V-50Hz	R134a	245	260
ACGE-50	-20°C -15°C	460	2075	665	3	0	3	303	230V-50Hz	R290	398	439
AGRE-125	-2°C +8°C	1250	2075	665	3	3	6	964	230V-50Hz	R134a	304	320
ACGE-125	-20°C -15°C	1250	2075	665	3	3	6	964	230V-50Hz	R290	907	899

CABINETS

We reserve the right to change specifications without prior notice.

- AISI-304 stainless steel exterior, rear side galvanized panel
- AISI-304 stainless steel interior, stamped bottom and rounded corners
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Key lock as standard
- **AGRE / ACGE** double glazed door + LEDS
- GN shelves made of plasticized steel wire, height adjustable
- AISI -304 adjustable legs, 135 to 210 mm
- Control panel and engine ventilation grill, removable
- Fan assisted condenser unit
- Fan assisted evaporator, with epoxi anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost, door open and high-temperature condensation alarms. Efficient management of energy consumption
- Operating temperature 32°C ambient

