



AP-750



AP-1002

mod.	range °C	length (mm)	height (mm)	depth (mm)	containers 40x60	slides sets	capacity (L)	voltage	refrigerant	frig. power W	power W
AP-750	-5°C -1°C	695	2100	840	7	7	645	230V-50Hz	R134a	485	491
AP-1002	-5°C -1°C	1395	2100	840	14	14	1404	230V-50Hz	R134a	684	677

We reserve the right to change specifications without prior notice.

- AISI-304 stainless steel exterior, rear side galvanized panel
- AISI-304 stainless steel interior, stamped bottom and rounded corners
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Key lock as standard
- Inner side of doors by stamped steel
- LED lighting
- Capacity for 60x40 shelves, containers or trays by stainless steel slides, height adjustable
- AISI -304 adjustable legs, 135 to 210 mm
- Control panel and engine ventilation grill, removable
- Fan assisted condenser unit
- Fan assisted evaporator, with epoxi anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m<sup>3</sup> density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost, door open and high-temperature condensation alarms. Efficient management of energy consumption
- Operating temperature 38°C ambient

CABINETS

