

# Product Code: EP700L2 41-145

## Half door freezer cabinet



The EcoPro G3 range of cabinets offers a combination of cutting-edge refrigeration technology, low running costs and reliability, making them the first choice for the foodservice professional.

#### Features & Benefits

- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Market leading usable capacity, now supplied with 4 shelves as standard making your money go further holds more than a conventional fridge
- This half door model is designed to save energy keep frequently used products in the top section for easy access, while keeping the bottom section shut to prevent cold air loss
- Operates efficiently in ambient temperatures of up to 43°C

Shelving		Base Fittings		Doors
Extra heavy duty shelving	Option	Castors 80mm	Standard	Half
4 shelves (GN2/1)	Standard	Legs 150mm	Option	Product Extras
Refrigeration		Electrical & Service	e Data	Helicoil Mains Lead
R290 - Energy Efficient	Standard	230/50/1	Standard	Energy
Integral Refrigeration System	Standard	Fuse Required (A)	10	
Less Condensing Unit	Option	Finish		AEC
	_			Nett Volume
Specification		s/steel ext, 304 s/s door & alu	int Standard	Energy Grade
Gross volume (ltrs)	600	304 S/S back for island sitting	g Option	Energy Efficiency Index
Freezer -18/-21°C	Standard			
Width (mm)	700			
Depth (mm)	855			
Height (mm)	2080			

Standard

Option

1161

479.9


49.47

В

### Footnotes

- Castors not available if product supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 100mm
- Depth with door open is 1500mm

### Energy Performance Data and information



#### Application

This appliance is intended for use in ambient temperatures up to 40°C **Safety** 

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

#### Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit our policies



The Refrigeration Experts

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.