



Product Code: EP700SL 41-766

Single door freezer short cabinet



The third generation of the EcoPro, the G3 cabinets are loaded with reliability, energy-saving, food safety and hygiene features.

Features & Benefits

- All the benefits of the standard G3, but this product can fit through a standard (1960 x 760) doorway without tilting
- Suitable for low ceiling height applications
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer - all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Market leading usable capacity, now supplied with 4 shelves as standard making your money go further – holds more than a conventional fridge
- Fully GN 2/1 shelving compatible
- Operates efficiently in ambient temperatures of up to 43°C

Shelving

Extra heavy duty shelving	Option
4 shelves (GN2/1)	Standard

Electrical & Service Data

230/50/1	Standard
Fuse Required (A)	10

Finish

304 s/s ext & int	Standard
------------------------------	----------

Base Fittings

Castors 80mm	Standard
Legs 150mm	Option

Product Extras

Helicoil Mains Lead	Option
----------------------------	--------

Energy

AEC	1161
Nett Volume	439.4
Energy Grade	B
Energy Efficiency Index	31.91

Refrigeration

R290 - Energy Efficient	Standard
Integral Refrigeration System	Standard
Less Condensing Unit	Option


Specification

Gross volume (Itrs)	550
Freezer -18/-21°C	Standard
Width (mm)	700
Depth (mm)	855
Height (mm)	1955

Footnotes

- Requires 100mm free space above product
- Depth with door open is 1500mm

Energy Performance Data and information



Application

This appliance is intended for use in ambient temperatures up to 40°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



The Refrigeration Experts

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.