



ICP202E - RATIONAL iCombi Pro - Model 20-2/1 - Electric Freestanding Combi Oven -67.9 kW The intelligent RATIONAL iCombi Pro 20-2/1 thinks, learns, watches and adapts, dynamically responding to requirements.

- Large 20 x GN 2/1 capacity, ideal for mass catering and for food service establishments with high output requirements
- Four intelligent assistants for climate management, cooking operation, production management, and cleaning
- iDensityControl delivers consistent and uniform results. At the same time, the intuitive operating concept provides the highest level of user support and less chance of errors
- iCookingSuite continuously checks the condition of the food against the desired result, calculates the cooking progress and intelligently adjusts the temperature to achieve. It also allows you to change the desired result, browning or cooking parameters during the cooking process

- iProductionManager optimises food production, simply place the dish on the display and it will show you what else you can produce at the same time
- iCareSystem 9 cleaning programmes, including the ultrafast interim clean in approx. 12 minutes
- WiFi interface for connected cooking and easy access to HACCP documentation

C manager.		Dawer and Darfarmana	
Summary		Power and Performance	
Brand	Lincat	Total Power kW	67.9
Range	RATIONAL	Temperature Range °C	30-300
Series	iCombi Pro	IP Rating	IPX5
Power Type	Electric	Temperature Control	Electronic
Jnit Type	Free-standing	Oven Rating kW	Steam connection = 54.0; Hot air
Available in UK Only	Yes		connection = 66.0
UK Warranty	RATIONAL 2 Years Parts and Labour		
•··· ·	Warranty		
Key Specifications		Capacity	
WRAS Approved	Yes	Gastronorm Capacity	20 x GN2/1
Гуре of Lighting	LED	Portions per Day	300-500
Number of Grids included	0		
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	1872	Requires Installation	Yes
Jnit Width (External) mm	1082	Requires Electrical Supply	Yes
Jnit Depth (External) mm	1117	UK 3 Pin Plug	No
Net Weight Kg	336	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	67,900
		Three Phase Amps	L1=100.0; L2=100.0; L3=100.0
		Three Phase Voltage	400
		Water Connection Pressure Bar	6
		Drain Connection	DN 50 mm
		Water Connection	3/4"





Shipping

 Packed Weight Kg
 369.6

 Packed Height cm
 204.3

 Packed Width cm
 119

 Packed Depth cm
 121.8

Available Accessories

60.70.464 RATIONAL Applicance Connection Kit - Model 6-1/1-20-2/1 - with Adapter for Model XS

6013.1103 RATIONAL Roasting and Baking Tray - Non-stick - GN1/1(325 x 530 mm)

6015.1103 RATIONAL Perforated Baking Tray - GN1/1(325 x530 mm)

6015.1165 RATIONAL Stainless Steel Perforated Container - GN1/1(325 x 530 mm) - 55 mm deep



Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm

A member company of

