### Staff Room Refrigeration

#### **Under-counter** Staff Room Refrigerator 158L

GDPA code SRS158W

SKU code 444410537









#### Key features

- Automatic defrost the air is continuously circulated around the inside of the fridge preventing any build up of ice inside the fridge compartment, meaning there will never be any need to defrost the product
- Reversible door the door can be hinged from either left or right so you can open for your convenience









## Removable door seal

Easy removal of your door seal for cleaning or replacing.

#### A+ energy rating

10% better efficiency than an A rated product for better kWh consumption and therefore cheaper to run.

# 2 year commercial warranty

All our staff room fridges come with a 2 year commercial warranty for peace of mind.

#### Energy efficient R600a gas

Using gas that is less damaging to the environment to help reduce our carbon footprint.



#### **Specification:** Under-counter Staff Room Refrigerator 158L

Gross Capacity (litres)	160
Net Capacity (litres)	158
Unit External Width (mm)	600
Unit External Depth (mm)	610
Unit External Height (mm)	850
Product Weight (kg)	34
Packed Width (mm)	630
Packed Depth (mm)	644
Packed Height (mm)	885
Packed Weight (kg)	36
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	
Temperature Range	+0°C to +10°C (set point tolerance + or - 2)
Colour	White
External Finish	White Plastic
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	White Plastic
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Domestic Style
Door Open Depth (mm)	1152
Replacement Door Seal	No
•	
Open Door Sensor Lock	Yes No
Adjustable Feet (number & position)	4 - All adjustable
Porthole	No
Porthole Size	No
Porthole Location	No
Temperature Display on Panel	No
Temperature Alarm	No
Remote Alarm Contacts	No
Audible Alarms	Yes
Visual Alarms	No
Number of Shelves	3
Number of Shelf Positions	6
Shelf Size (mm) (WxDxH)	TBC
Shelf Material	Glass
Number of Baskets	1
Basket Material	Plastic
Basket Size (mm) (WxDxH)	TBC
Interior Light	Yes
Light Type	LED
Light Activation	Door Switch
Fan	Yes
Spark Free	No
Defrost setting	Auto (Off Cycle)
Controller Type	Manual Thermstat
Number of Probes	1
Probe Type	Air
Ambient Temperature Range	10 to 32
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	No
Voltage Supply	220 - 240
Insulation Thickness (mm)	55
Insulation Type	High Density Polyurothane Foam
Blowing Agent	Cyclopentane
Anti Microbial Handle	No
Wall Brackets	No
Optional Drawer System	No
Optional Digital Lock	No
Other Door Option	No

