



▶ Up to 8 x 2/3 GN or 442 x 320 mm



▶ Distance between the drawers: 75 mm



- Power load: 2 kW | 230 V | 50-60 Hz
- Equipment connection: Pluggable
- Temperature range: 30 °C to 60 °C
- Distance between trays: 75 mm
- Type of drawers: Crosswise
- Properties: Water bowl for air humidification
- Format drawers: 2/3 GN
442 x 320 mm
- Material: CNS 18/10
- Important information: -
- Control lamp: ON/OFF
- Number of drawers: 8
- Size: W 700 x D 600 x H 960 mm
- Weight: 44 kg

Fermenting cupboard 823HO

Add on Products

Power cleaner F1L, set of 2



- Designed for: Stubborn dirt, especially in kitchens
Grill and combi steamer cleaning (without cleaning system)
- Content: 2 x 1 litre
- Model: Liquid
High concentrate
- Ph level: 13,5
- HACCP compliant: Yes
- Chlorine-free: Yes
- Phosphate-free: Yes

Code-No. 173078
GTIN 4015613731926

Perforated tray 2/3-AL



- Diameter perforation: 3 mm
- Gastronorm: 2/3 GN
- Edge: 4 sides, cover
- Silicone coating: No
- Material thickness: 1,5 mm
- Perforation: Yes
- Temperature resistant to: 260 °C
- Material: Aluminium
- Important information: -
- Size: W 354 x D 325 x H 10 mm
- Weight: 0.36 kg

Code-No. 100417
GTIN 4015613734729

Perforated tray 2/3-SI



- Diameter perforation: 3 mm
- Gastronorm: 2/3 GN
- Edge: 4 sides, cover
- Silicone coating: Yes
- Material thickness: 1,5 mm
- Perforation: Yes
- Temperature resistant to: 260 °C
- Material: Aluminium
- Important information: -
- Size: W 355 x D 325 x H 10 mm
- Weight: 0.41 kg

Code-No. 100425
GTIN 4015613734736