NE-1880 / NE-3280 GASTRONORM

Panasonic ideas for life



UP TO 3200W OF POWER FOR LARGE VOLUME COOKING

These robust ovens handle the most rigorous of duties. With power of up to 3200W plus the large capacity, they can sustain consistently fast output - making them the ideal choice for cooking multiple dishes simultaneously.

The large capacity NE-3280 Gastronorm Oven can cook 5 portions of cannelloni (1.58kg multiportion) in just 5 minutes from chilled.

Power Matters, Capacity Matters, EVERYTHING MATTERS.

www.panasonic.co.uk Sales Office: 01344 476516

NE-1880 / NE-3280 GASTRONORM

Panasonic ideas for life

- NE-1880 (1800W), NE-3280 (3200W)
- 4 power levels
- Quad Emission. 4 magnetrons and rotating wave guides for fast and even heating
- Positive action dial control timer
- Stainless steel body and cavity
- · Removable shelf
- Pull-to-open drop down door
- Cycle counter records number of operations
- Programmable touch controls
- 16 programs to include 2 and 3 stage heating
- Program lock allows one touch operation
- Manual heating with repeat function
- Accommodate Gastronorm 1/1 (530 x 325mm) containers in 2 layers

PLACEMENT OF YOUR OVEN

- Oven must be placed on a flat, stable surface. For proper operation, the oven must have sufficient air flow.
 - A gap of at least 5cm (2") must be available at the right and left hand sides and back wall of the oven.
 - A minimum space of 20cm (8") must be left above the oven and the 2 exhaust vents at the rear.
- Do not place the oven on a shelf directly above or beside a gas or electric hob or cooker. This may cause damage to the oven.
 - It is dangerous to position this oven on a shelf which is so high that food and accessories cannot be safely removed by the user.
- Do **NOT** attempt to stack these ovens.

PROGRAM LOCK

To allow one touch operation, especially for applications such as sites where a
variety of regular programs are used, fast food sites and where de-skilling has
been implemented.

PROGRAMMABLE MEMORY PADS

 The power level and heating time for regular dishes can be programmed into the 16 memory pads for speed of operation and consistent results.

2 & 3 STAGE HEATING


 Allows the power level to change during heating e.g. 'Defrost' for 3 minutes, then 'High' for 1 minute in a single operation thus freeing the operator from constant attendance to reset controls.

Power Supply

NE-1880 20 amp, hardwired, NE-3280 30 amp, hardwired

| TECHNICAL SPECIFICATIONS | | | |
|---------------------------|-------------------------------|-------------------------|--|
| | TOUCH | TOUCH | |
| Model | NE-1880 | NE-3280 | |
| Power Source | 230-240V / 50Hz, Single phase | | |
| Power Requirement | 3400W, 14.8amp | 5220W, 22.3amp | |
| Output Power (W) IEC 705* | | | |
| High | 1800W | 3200W | |
| Medium | 900W | 1600W | |
| Low | 340W | 340W | |
| Defrost | 170W | 170W | |
| Stand | Zero W | Zero W | |
| Frequency MHz | 2450MHz | 2450MHz | |
| Outer Dimensions (wxdxh) | 650 x 526 x 471mm | | |
| Oven Dimensions (wxdxh) | 535 x 330 x 250mm | | |
| Weight (kg) | 54kg | 65kg | |
| Timer (min) | | | |
| High | 15 min | | |
| Medium | 15 min | | |
| Low | 60 min | | |
| Defrost | 60 min | | |
| Stand | 60 min | | |
| Programs | 16 | | |
| Memory | 3 stage | | |
| Cubic Capacity | 44 litres (1.56 | 44 litres (1.56 cu. ft) | |

* IEC 705 – 88 Test Procedure Specifications subject to change without notice



Quadruple power feed for more consistent even cooking



Multiportion cooking



Plated meals