



Model T5A

SOFT SERVE FREEZER

SINGLE FLAVOR, COUNTERTOP, DIGITAL CONTROL



Most Compact & Versatile single flavour countertop model with pump feed option for soft ice cream & frozen yogurt



FAST FREEZE DOWN

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption



DIGITAL CONTROL AND DISPLAY

Digital control provides access to system settings and displays critical system information



AUTO PROGRAMMING

Allows automatic switching of operation modes based on preset schedules



STANDBY

Maintains product temperature in both mix hopper and freezing cylinder below 4.4 $^{\rm Q}$ C (40 $^{\rm Q}$ F) overnight



HOPPER AGITATOR

Maintain product consistency and prevent product separation



DIRECT DRIVE TRANSMISSION

Eliminates consumable moving parts and increases transmission efficiency



DEFROST FOR CLEANING

Increases efficiency during cleaning by heating frozen product in cylinder



SAFETY PROTECTIONS

- Low temperature and motor overload shut-off to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating



PASTEURIZATION FEATURE

Allows product to stay fresh in the machine for up to 21 days

MOST **COMPACT** AND **VERSATILE** SINGLE FLAVOR COUNTERTOP MODEL FOR SOFT SERVE ICE CREAM AND FROZEN YOGURT


MAXIMISE YOUR PROFITS






MODEL T5A

SOFT SERVE FREEZER





















SPECIFICATIONS

Flavours		1
Freezing Cylinders		1 x 1.2L
Mix Hoppers		1 x 8L (5L for A)
Output Capacity (80 grams)		150 serves/hr
Clearance Requirements		150mm/6" on back
WEIGHT	KG/LB (Gravity)	KG/LB (Pump)
Net	90 / 198	100 / 220
Shipping	102 / 225	112 / 247
Volume	0.27 CBM / 9.53 CBF	
DIMENSIONS	NET (MM/IN)	SHIPPING (MM/IN)
Width	284 / 11.2	380 / 15.0
Depth	754 / 29.7	800 / 31.5
Height	755 / 29.7	900 / 35.4
ELECTRICAL	13 Amps	

FEATURES

CONTROL SYSTEMS	SINGLE DIGITAL
REFRIGERATED HOPPERS	<u> </u>
HOPPER AGITATOR OPTIONAL	<u> </u>
TEMPERATURE DISPLAY	<u> </u>
STANDBY MODE	V
AUTO CLOSING DISPENSING VALVES	V
DISPENSING SPEED CONTROL	<u> </u>
LOW MIX INDICATOR LIGHT & ALARM	V
LOW TEMPERATURE PROTECTION	V
MOTOR OVERLOAD PROTECTION	V
HIGH PRESSURE PROTECTION	V
DEFROST & QUICK REFREEZE	V
SOFT START (50HZ ONLY)	V
DIRECT DRIVE PUMP (A ONLY)	V