KBS11A

106

PASTRY REF.COUNTER TOP W/SPLASHBACK, 1 DOOR 60x40

18-10 st/steel refrigerated counter,insulated all- in-one structure.Insulated door,s/s handle.Cooling system with finned evaporator and electric fan. Automatic defrosting and autom.condensation drain. Electronic thermometer-thermostat.S/s adjust.feet. Tropic.+43°C. Working top with rear splashback.



((

General information

Supplier/producer 's name	SAGI
Series	Pastry & Bakery
Supplier's model identifier	KBS11A
Category	counter cabinet
Туре	refrigerated counter
Line	pastry & bakery - EN 60x40

Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	С
Energy consumption E24, kW/h	2,77
Energy consumption/year, kW/h	1011
Method for energy consumption	EN 16825
Energy Efficiency Index	44,37
Net usable volume, It	120
Volume, gross, lt	193
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\text{C}$
Refrigerant/GWP	R404A/3922
Refrigerant charge, kg	0,28
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

PASTRY REF.COUNTER TOP W/SPLASHBACK, 1 DOOR 60x40





PASTRY REF.COUNTER TOP W/SPLASHBACK, 1 DOOR 60x40

KB



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	304
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,3
nstruction features	
Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	55
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	7/75
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condense
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Worktop	worktop 60 mm thick in AISI 304 stainless steel (15/10mm), with soundproofing lining; with splashba
Equipped with	1 door
ntrol and functions	
Kinf of control	thermometer-thermostat
Display	digital

Conf

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Shelf's dimensions, cm	EN 60x40
Shelves and couple of guides	7 pair of AISI 304 stainless steel runners for section

Dimensions and weights

Packing (LxDxH), cm	115x82x115
Dimensions (LxDxH), cm	110x80x96,5
Gross Weight (kg)	115
Net Weight (kg)	105



